



AD A 0 97834

COMPOSITES FOR ELECTROCHEMICAL TECHNOLOGY PART I. SURVEY OF ELECTRODE CORROSION STUDIES FOR LEAD-ACID BATTERIES

BY I. A. ANGRES R. A. SUTULA

RESEARCH AND TECHNOLOGY DEPARTMENT

SEPTEMBER 1980



Approved for public release, distribution unlimited.



NAVAL SURFACE WEAPONS CENTER

Dahlgren, Virginia 22448 • Silver Spring, Maryland 20910

TE FILE COP

81 4 16 029

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FO
12 GOVT ACCESSION NO 12 FR-80-239 - PT-1 A D-A 091	3 RECIPIENT'S CATALOG NUMBER
4. IITLE (and Subjute)	5. TYPE OF REPORT & PERIOD CO
PART I. SURVEY OF ELECTRODE CORROSION STUDIES	FY 80
FOR LEAD-ACID BATTERIES	6. PERFORMING ORG. REPORT NUM
7. Author(*) 1. A./Angres, R33	S. CONTRACT OR GRANT NUMBER
R. A. /Sutula, R32	(16) F54594
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT,
Naval Surface Weapons Center	AREA & WORK UNIT NUMBERS
White Oak	62761N: SF54-594;
Silver Spring, MD 20910	SF54-594-594 9R37B
11. CONTROLLING OFFICE NAME AND ADDRESS	12 REPORT DATE
(14.41)	SEP BU
(12)24	24
MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	15. SECURITY CLASS. (of this report
(9) Technical reption	Unclassified
J 1 3 3 10 10 1 3 W 1 1 1 E p 113	15a. DECLASSIFICATION DOWNGRA
"Approved for public release; distributi	on unlimited."
"Approved for public release; distributi 17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different fr	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G	om Report)) rid materials
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G Lead-acid batteries Accelerat	om Report)
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G	om Report)) rid materials
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G Lead-acid batteries Accelerat Lead Metal Matrix Composites	om Report)) rid materials ed corrosion
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G Lead-acid batteries Accelerat Lead Metal Matrix Composites 20. ABSTRACT (Continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block number continue on reverse side if necessary and identify by block nu	om Report)) rid materials ed corrosion
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G Lead-acid batteries Accelerat Lead Metal Matrix Composites	om Report) rid materials ed corrosion ectrodes which are
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery Galead-acid batteries Accelerat Lead Metal Matrix Composites 20. ABSTRACT (Continue on reverse side if necessary and identify by block number Corrosion methods used to screen lead el	om Report) rid materials ed corrosion ectrodes which are
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from the supplementary notes 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery G Lead-acid batteries Accelerat Lead Metal Matrix Composites 20. ABSTRACT (Continue on reverse side if necessary and identify by block number Corrosion methods used to screen lead el potential candidates for use in lead-aci	om Report) rid materials ed corrosion ectrodes which are
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery Galead-acid batteries Accelerat Lead Metal Matrix Composites 20. ABSTRACT (Continue on reverse side if necessary and identify by block number Corrosion methods used to screen lead el potential candidates for use in lead-acid	om Report) rid materials ed corrosion ectrodes which are
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from 18. Supplementary notes 19. KEY WORDS (Continue on reverse side if necessary and identify by block number Corrosion Battery Galead-acid batteries Accelerat Lead Metal Matrix Composites 20. ABSTRACT (Continue on reverse side if necessary and identify by block number Corrosion methods used to screen lead el potential candidates for use in lead-acid	om Report) rid materials ed corrosion ectrodes which are

JAN 73 14/3 5'N 0102-LF-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

FOREWORD

This report briefly describes corrosion methods used to screen lead electrodes which are potentially useful for submarine lead acid batteries.

J. R. DIXON
By direction

Accession For

NTIS GRARI
DTIC TIB
Unanneuroed
Justification

By
Distribution/
Availability Color
Availability Color
Epoch 1

ACKNOWLEDGEMENT

This work was supported by Mr. M. Kinna (NAVSEA 62R) through the Metal Matrix Materials Block under the direction of Dr. John V. Foltz. We are particularly indebted to Mr. A. Himy (NAVSEA 543) for his technical advice and suggestions.

CONTENTS

	Page
FOREWORD	1
ACKNOWLEDGEMENT	2
INTRODUCTION	5
CORROSION CONSIDERATIONS	. 6
CONCLUSION	. 13

ILLUSTRATIONS

rigure		Page
1.	DIAGRAM OF APPARATUS	. 8
2.	DIAGRAM OF APPARATUS FOR INVESTIGATING THE ANODIC CORROSION OF METAL MATRIX MATERIALS	. 11
Table	TABLE	Page
I,	POTENTIALS OF VARIOUS ELECTRODES REFERRED TO THE Hg, Hg SO ELECTRODE IN 40.8% H2SO AT 20°C	. 9

4

INTRODUCTION

This report provides a brief review of corrosion literature to establish a data base on corrosion studies for lead electrodes.

The main storage battery in nuclear submarines is lead-acid, and serves the following purposes:

- Provides a ready source of standby power capable of sustaining ship or nuclear reactor vital auxiliaries without interruption of service in the event of loss of normal power sources; and
- 2. In the event of a nuclear reactor scram, it sustains submerged ship operations to re-start the nuclear reactor. This includes providing propulsion, life support, ship and nuclear reactor auxiliary power.

The importance of the main storage battery in maintaining the reliability of the nuclear propulsion plant cannot be overemphasized.

The electrode grids of most lead-acid batteries are made from alloys such as lead-antimony, lead-arsenic, or lead-calcium, that possess better mechanical strength and are easier to handle than pure lead.

Present-day nuclear submarine batteries employ grids made of lead-calcium alloys. However, these grids suffer serious mechanical failure as a result of corrosion. After about 66 months of service, the positive grid of the nuclear submarine battery loses its strength and expands, causing battery failure.

The grid material of choice, from an electrochemical standpoint, is pure lead metal. It is known that pure lead has many desirable properties:

- 1. High hydrogen overpotential; 1
- 2. Avoids adverse electrochemical side effect of alloying ingredients; and
- 3. Excellent corrosion resistance to sulfuric acid. Pure lead, however, lacks the tensile and creep strength to serve alone as a grid material.
- 1. Hampel, C. A., "The Encylopedia of Electrochemistry", Reinhold, New York (1964) pg. 869.
- 2. Perkins, J., Pokorny, J. L., Coyle, M. T., AD-A 032-299 "A Review of Materials and Mechanisms which affect the performance of Lead-Acid Batteries", Oct. 1976.

Exploratory development has shown that metal matrix composite grids made from pure lead reinforced with non-metallic fibers will combine the desirable electrochemical properties of pure lead with the great mechanical strength of the fibers.

Since corrosion studies are used to screen the composite materials for use as grids in lead-acid batteries, a short literature review on corrosion of lead and its electrodes including experimental details are described below.

CORROSION CONSIDERATIONS

Lead and its alloys are used in a variety of lead-acid battery designs and applications. Therefore, it is necessary to examine the behavior of a given alloy under the conditions of its prospective use, for example float charge.

Lander was the first to study the anodic corrosion of lead in detail. Combining a thermodynamic and kinetic approach, he related the mechanism of the positive plate reactions to the actual conditions of battery service. Lander's work showed that the grid of the Pb/PbO₂ electrode is passivated at a potential corresponding to mild overcharge; which is encountered in battery-"Float" service. The original work of Lander³ showed that at constant potentials in the range 0.1 to 1.0 volt, tetragonal PbO is formed in contact with lead in sulfuric acid solutions. An outer layer of PbSO₄ is formed, probably by chemical reaction between H₂SO₄ and the PbO layer. The corrosion rate in this voltage range increased with increasing temperature and with decreasing acid concentration. The latter effect is explained by showing a linear relation between rate and the square of the activity of water in the electrolyte. At potentials from 1.20 to about 1.50 a protective film is formed, presumably consisting of PbO₂.

Subsequently, Lander 4 showed that PbO_2 undergoes a solid phase reaction with Pb to form tetragonal PbO. A mechanism involving the Volta effect is proposed. A contact potential between Pb and PbO_2 may be an important part of the cell potential and explain self-discharge and the discharge reaction at the positive plate.

An intermediate film of PbO₂ is formed by the corrosion process which does not cycle completely to PbSO₄. Because of this, it retains its compact nature and may in large measure be responsible for slowing down grid corrosion.

Grid growth appeared to be proportional to the depth of corrosion after an initial period. The initial period and the rate of growth are probably charactistic of the tensile strength or creep resistance of the metal.

The mechanisms governing rate have not been determined in all the potential ranges concerned; indeed, the whole picture is rather complicated because of the number of reactions occurring. The following reasoning can be ascertained from Lander's work: 5

- 3. Lander, J. J., <u>J. Electrochem. Soc.</u>, 98, 213 (1951)
- 4. Lander, J. J., ibid; pg. 98, 220 (1951)
- 5. Lander, J. J., <u>ibid</u>; pg. <u>103</u>, 1 (1956)

- Formation of lead dioxides by the reaction, Pb + 2H₂O → PbO₂ + 4H⁺ + 2e⁻, is the first step in the corrosion process above the reversible potential for that reaction. It is unstable both on chemical and electrochemical grounds at the lower potentials and goes to lead monoxide and lead sulfate.
- 2. A voltage limit above which the solid-phase reaction, Pb + PbO₂ = 2PbO, cannot go has been shown to be about +1.58v to the standard hydrogen electrode. This voltage marks the appearance of lead dioxide in the corrosion product and is characterized by a peak in the corrosion-rate vs potential curve which separates the kinetic behavior of the corrosion processes. At more noble potentials, just below the reversible positive-plate potential, corrosion rates are limited by penetration of the positive-plate-discharge-reaction into an underlying lead dioxide film. This (pretration) is controlled by diffusion of SO₄ through a porous film of mixed lead dioxide and lead sulfate. At slightly less noble potentials, diffusion control gives way to a relatively rapid process because the solid phase reaction begins to take place and the lead dioxide film is attacked from both sides.
- 3. Above the reversible PbO2/PbSO4 potential, corrosion rates fall off very rapidly to extremely low values, because a protective lead dioxide film is built up. Rates in this potential range do not vary with potential at room temperature within experimental error, but they do increase with increasing temperature and decreasing acid concentration.

The experimental details of Lander's work are as follows: Granular lead (purity about 99.97%) was melted in a clean glass beaker, cast into a steel mold, and cold rolled to a thickness of 0.051 cm (0.02 in.) between polished steel rolls. Samples were always cut to the same dimensions giving a total area of 34 cm² and were maintained at several constant potentials in sulfuric acid solutions in the range covering about one volt below the reversible potentials for the PbO2 - PbSO4 couple. The sulfuric acid was used in concentration of 10, 30, and 40 percent by weight, and two constant temperatures: 30° and 50° C were employed. The rates of attack were followed either by stripping the film in ammonium acetate solution and determining weight loss directly or by recording the currents flowing through the samples. By checking measured weight loses against those calculated from Faraday's law, it was established that the law, calculated for the reaction: Pb \rightarrow Pb²+ + 2e- applies at potentials below those for PbO2, formation. X-ray analyses of the film substance were also obtained.

The circuit diagram of the apparatus used for maintaining constant potential is shown in Figure 1. A resistor R_1 , consisting of several feet of copper wire, was connected in series with the variable resistors R_3 and R_4 , so that currents producing potential drops up to 1.1 volts across R_1 could be made to flow. B, the sample to be anodized, was contained in a beaker of sulfuric acid electrolyte, and could be connected to any position on R_1 through R_2 , a two-ohm resistor, from which leads ran to a G.E. potentiometer recorder. A and A' were sections of positive plate from a lead-acid cell, having a capacity such that currents of the magnitude drawn by the samples produced no polarization. They were connected by switches S_1 and S_2 to either end of the slide wire so that a given potential, anodic or cathodic to that of the PbO2 plate, could be applied to the sample. C was a mercury-mercurous sulfate reference electrode, the tip of which was kept within 1 mm of the sample. The contribution to the potential by the ohmic resistance




FIGURE 1 DIAGRAM OF APPARATUS

between sample and reference electrode was estimated to be considerably less than 1 mv for a current of 10 ma. The reference electrode and the sample were connected to a Rubicon Null-point potentiometer. The sample potential was adjusted manually by sliding the contact from R_2 along R_1 and by adjusting the resistors R_3 and R_4 . Potentials were controlled to within ± 0.01 volt and variations within this range did not introduce significant errors. Current-time curves were plotted from the record, and weight-loss vs. time curves were then calculated using small increments of the area under the curve and Faraday's law.

All voltages are referred to the mercury-mercurous sulfate electrode in 40.8 percent sulfuric acid at 20°C, which has a potential of +0.566 to the standard hydrogen electrode. For purposes of orientation the reversible potentials of the several couples under the various experimental conditions with respect to this electrode are given in Table I. Standard potentials are also included. These values were all calculated from the data of Harned and Hamer⁶ except for the Pb, PbO, and Pb, Pb(OH) 2 couples for which E°'s were calculated using the free energy data from Latimer⁷ and the other values using the Nernst equation for the reactions:

Pb +
$$H_2O \longrightarrow PbO + 2H^+ + 2e$$

and

Pb +
$$2H_2O \longrightarrow Pb(OH)_2 + 2H^+ + 2e$$

Table I. Potentials of various electrodes referred to the Hg, Hg_2SO_4 electrode in $40.8\%\ H_2SO_4$ at $20^{\rm OC}$

			H ₂ SO ₄				
Electrode	Eo	10%		30%		40%	
		30 _o C	50 ⁰ C	30°C	50 ⁰ C	30 ⁰ C	50°C
PbO ₂ , PbSO ₄	+1.685	+1.063	+1.058	+1.135	+1.131	+1.181	+1.177
Hg, Hg ₂ SO ₄	+0.615	+0.104	+0.099	+0.038	+0.031	+0.000	-0.004
Pb, PbO	+0.250	-0.348	-0.351	-0.306	-0.306	-0.280	-0.277
Pb, Pb(OH) ₂	+0.242	-0.357	-0.360	-0.312	-0.312	-0.280	-0.277
Pb, PbSO ₄	-0.355	-0.865	-0.873	-0.933	-0.942	-0.970	-0.979

Thomas and Haring 8 established that by static discharge the Pb-Sb alloy sulfates in approximately 1/9 of the time required for pure Pb and 1/10 the time required for the Pb-Ca alloy. They concluded that anodically and cathodically, the behavior of

Harned, H. S., and Hamer, W. J., J. Amer. Chem. Soc., 57, 33 (1935)

^{7.} Latimer, W. M., "Oxidation Potentials," pp 304-305, Prentice Hall Inc., NY (1938)

^{8.} Haring, H. E., Thomas, U. B., Trans. Electrochem. Soc., 68, 293 (1935)

the Pb-Ca alloy is similar to that of pure reac but quite distinct from that of the Pb-Sb alloy.

With respect to carbon-reinforced lead electrodes, only preliminary work has been done by Gould, and the results are encouraging. In summary, Gould found that the best results were obtained with the HM/PVA-3000 graphite-fiber composite rods with 15 mil electroplate of lead. The rods completed 75 days on test at 71°C which would be equivalent to 2250 days (6.14 years) at room temperature. The maximum depth of corrosion was found to be three mils.

The apparatus used in these corrosion studies are shown in Figure 2. The constant potential was supplied by a custom-built multistation potentiostatic voltage regulator. A primary reference voltage was provided by a Lamda LCS-2-01 power supply with each individual station provided with a 20 turn pot for fine regulation. The sensing and current leads were separate. The voltage was checked and adjusted as required at 24-hour intervals. The corrosion studies were conducted at 71°C in 1.285 specific gravity sulfuric acid with constant potential of 1.226 v anodic to the mercury-mercurous sulfate electrode.


In comparing Lander's experimental set up and the experimental set up of Gould it is found that the Gould approach provides corrosion data in terms of life-stability at a much more rapid rate than Lander's approach. Lander's approach is closer to the actual corrosion a battery experiences during charge-discharge. However, it appears that a much longer time is needed to get the necessary data for final evaluation of lead composite samples.

The data obtained from the accelerated anodic corrosion studies at 71°C was assumed to follow the Arrhenious equation,

$$\frac{1}{T_1} - \frac{1}{T_2} = K \log \frac{I_2}{I_2}$$
 (1)

where I represents the rate of any specific chemical process, and extrapolated to 25°C to obtain the service life of the composite electrode. Extrapolation of anodic corrosion data at high temperatures to room temperature must be taken with "a grain of salt." It is possible that at the high temperature the reactions and products may be substantially different than those at 25°C. Without a correlation between the 71 and 25°C temperature data, it is not possible to put any confidence in the values obtained for service life of the electrode. The accelerated anodic corrosion tests at 71°C can be used as a relative method to screen potential fiber reinforced lead composites. Since all electrodes are treated in the same way during the corrosion test, then those electrodes that last the longest would tend to give the longest service life at 25°C. Thus, it is evident that corrosion data at 25 and 35°C must be obtained to determine whether the data obtained from the accelerated anodic corrosion tests at 71°C can be modeled by equation (1) with any confidence in the service life values at 25°C.

Mao, G. W., Fiedler, A. F., "Feasibility Study for Utilization of Fiber Reinforced Lead Composites in Naval Hardware Applications," Report No. NSWC-76-C-0215-U, 15 November 1977.



- 1. WORKING ELECTRODE Pb/Ca OR LEAD COMPOSITE
- 2. ION SELECTIVE ELECTRODE
- 3. REFERENCE ELECTRODE Hg/Hg2 SO4
- 4. COUNTER ELECTRODE Pb

FIGURE 2 DIAGRAM OF APPARATUS FOR INVESTIGATING THE ANODIC CORROSION OF METAL MATRIX MATERIALS

Therefore, using the apparatus of Figure 2 we recommend that accelerated anodic corrosion tests on lead, lead alloys, and fiber reinforced lead composites be performed at 25, 35 and 70° C. By performing the accelerated anodic corrosion test at three temperatures it will be possible to determine what correlation exists between the 70° and 25° C temperature data.

CONCLUSION

Accelerated anodic corrosion tests can be used to evaluate the service life of lead-acid battery electrodes provided a correlation exists between high and room temperature data. Without such a correlation the accelerated anodic corrosion tests can only be used as a relative method to screen potential fiber reinforced lead electrodes.

DISTRIBUTION

	Copies		Copies
Office of Deputy Under Secretary		Commander	
of Defense for Research and		Naval Sea Systems Command	
Engineering		Attn: Mr. M. Kinna, Code 62R	1
Staff Specialist for Materials		Dr. H. Vanderveldt,	
and Structures		Code 0352	1
Room 3D1089, The Pentagon		Mr. G. Sorkin, Code 035	1
Attn: Mr. Jerome Persh	1	Dr. J. W. Murrin, Code 0331	1
Washington, DC 20301		Mr. A. Himy, Code 5433	1
-		Code 09G32	2
Defense Advanced Research Projects		Code 03B	1
Agency		Code 0841B	1
1400 Wilson Blvd.		Washington, DC 20362	
Attn: Dr. A. Bement	ì	-	
Arlington, VA 22209		NETCO	
		2225 E. 28th Street	
Naval Material Command		Attn: Mr. L. Davis	
Department of the Navy		Long Beach, CA 90806	1
Attn: Mr. W. Greenert, MAT 08D	1	-	
Mr. W. Holden, MAT 08E4	1	Areospace Corporation	
Washington, DC 20360		Ivan A. Getting Laboratories	
		300 S. Douglas Street	
Office of Naval Research		Attn: Dr. E. Kendall	1
800 N. Quincy Street		Mr. W. Pfeifer	1
Attn: Dr. B. MacDonald, Code 471	1	Mr. W. C. Riley	1
Dr. G.A. Neece, Code 472	1	El Segundo, CA 95085	
Code 715	1	_	
Arlington, VA 22217		Commander	
		Naval Air Development Center	1
Naval Research Laboratory		Attn: Dr. E. McQuillen	i
Attn: Dr. S. C. Sanday, Code 6370	1	Dr. G. London	•
Dr. I. Wolock, Code 8433	1	Warminster, PA 18974	
Dr. H. Chaskelis, Code 8431	1	_	
Dr. A. C. Simon, Code 6130	1	Commander	
		David Taylor Naval Ship	
		Research and Development	
		Center	1
		Attn: Mr. J. Gudas, Code 2813	1
		Dr. W. Lukens, Code 2822	1
		Mr. J. Kelly, Code 2803	1
		Mr. A. B. Neild, Code 2723	ì
		Annapolis, MD 21402 Code 2724	•

	opies		Cories
Commanding Officer		LWA Composite Specialties, Inc.	
Air Force Materials Laboratory Wright-Patterson Air Force Base		21119 Superior Street	,
Attn: Mr. M. Duhl, Code MB	1	Attn: Mr. J. Dolowy	1
Mr. T. Ronald, Code LLS	1	Chatsworth, CA 91311	
•	_	A.A. and A. Camman Am. Ton.	
Dr. W. S. Bishop, Code POE-1		Materials Concepts, Inc.	
Dr. J. Lander, Code FOE-1	1	2747 Harrison Road	,
Dayton, OH 45433		Attn: Mr. S. Paprocki	1
Department of the Army		Columbus, OH 43204	
AMMEC OF THE ATMY		Materi 1 (pietus Competies	
Attn: Dr. A. Levitt	1	Material Science Corporation	
Mr. J. Greenspan	1	Blue Bell Office Campus	
Dr. F. Larson	1	Merion Towle House Attn: Dr. B. W. Rosen	•
	1		1
Watertown, MA 02172		Blue Bell, FA 19427	
NASA/Langley Research Center		U.S. Army Lesearch Office	
Attn: E. Mathauser, Code MS188A	1	Associate Director, Metallurgy	
Dr. T. Bales	1	and Materials Science Division	
Dr. D. Tenney	1	P.O. Box 1321	
Hampton, VA 23365		Attn: John C. Hurt	1
•		Triengle Park, NC 27709	
NASA Headquarters		,	
600 Independence Avenue		Ballistic Missile Defense Officer	
Attn: G. Deutsch	1	BML-ATC	
Washington, DC 20546		P.O. Box 1500	
•		Attn: M. L. Whitfield	l
NASA Lewis Research Center		Huntsville, AI 358C7	
2100 Brookpark Road		•	
Attn: Mr. R. A. Signorelli	1	Commanding Officer	
Dr. J. S. Fordyee,		Air Force Flight Dynamics	
Code MS309/i	1	Laboratory	
Cleveland, OH 44135		Wright-Patterson Air Force base	
Exxon Enterprise, Inc.		Arth: D. Foselius	1
Project Manager		I. Felley	1
Old Buncombe Road and Poplar Drive		Tayton, CH 45433	
Attn: Jack L. Cook	1		
Greer, SC 29651	•		
THE THREE TO SECULAR			

	Copies		Copies
SAMSO (YCPC)		Naval Ordnance Station	
P.O. Box 92960, LAAFS		Project Manager	
Worldway Postal Center		Southside Drive	
Attn: LTCOL H. L. Staubs	1	Attn: Howard R. Paul	1
Los Aggeles, CA 90009		Louisville, KY 40150	
The Pentagon		Department of the Navy	
Project Officer, OSD (MRA&L)-WR		Strategic Systems Project Office	
Room 2B323		Crystal Mall No. 3	
Attn: William G. Miller	1	Attn: G. Needham, Code 273	1
Washington, DC 20301		LCDR F. Ness, Code 234 LCDR H. Nakayama,	1
Johns Hopkins Yniversity		Code 272	1
Applied Physics Laboratory		Washington, DC 20362	
Section Supervisor-Structures			
Johns Hopkins Road		AF Weapons Laboratory	
Attn: William Caywood	1	Kirtland AFB	
Library	1	Attn: Charles Stein	1
Laurel, MD 20810		Albuquerque, NM 87115	
Lockheed Missile and Space		Lockheed Missiles & Space	
Company, Inc.		Company, Inc.	
Bldg. 154		1111 Lockheed Way	•
P.O. Box 504		Attn: Henry H. Armstrong	1
Attn: A. C. Johnson, Dept. 81-22 G. B. Pinkerton,	1	Sunnyvale, CA 94086	
Dept. 81-22	1	Commander	
J. T. McGrath, Dept. 81-12	ī	Naval Air Systems Command	
Sunnyvale, CA 95020	-	Attn: Mr. R. Schmidt,	
, ·, ·		Code 52031A	1
Fiber Materials, Inc.		Dr. H. Rosenwasser,	
Director, Research & Development		Code 310C	1
Biddeford Industrial Park			
Attn: Roger I. Pepper		Aluminum Company of America	•
Biddeford, ME 04005		Attn: Thomas B. Gurganus	1
		Alcoa Center, PA 15069	

	Copies		Copies
Atlantic Research Corporation		Lockheed Corporation	
5390 Cherokee Avenue		P.O. Box 551	
Attn: Jerry L. Fields	1	Bldg. 61, Dept. 03/10	
Jay Baetz	1	Attn: M. A. Steinberg	1
Alexandria, VA 22314		Burbank, CA 91520	
E. I. Du Pont De Nemours & Co. (Inc.)		Lockheed Missiles and Space Company, Inc.	
Pioneering Research Division		P.O. Box 504	
Experimental Station		Dept. 62-92, Bldg. 154	
Attn: Ashok K. Dhingra	1	Attn: Elliott Willner	1
Wilmington, DE 19898		Sunnyvale, CA 94086	
AME RCOM		Hughes Aircraft Company	
8946 Fullbright Avenue		Blg. 6/MML Sta. D 147	
Attn: Robert Fisher	1	Attn: R. W. Seibold	1
Chatsworth, CA 91311		Culver City, CA 90203	
United Technologies Research Cente	er	Air Force Materials Laboratory	
Attn: Karl M. Prewo	1	Nonmetallic Materials Division	_
East Hartford, CT 05108		Attn: R. M. Neff WPAFB, OH 45433	1
Sandia Labortories		WAD, 01. 13433	
Attn: William R. Hoover	1	The Boeing Vertol Company	
Livermore, CA 94550		P.O. Box 16858, P62-06	_
		Attn: R. L. Pickney	1
General Dynamics		Philadelphia, PA 19142	
Convair Division			
P.O. Box 80847		AVCO Specialty Materials 2 Industrial Avenue	
Attn: N. R. Adsit	1	Attn: Paul R. Hoffman	
San Diego, CA 92138		Lowell, MA 01851	
Vought Corporation			
Advanced Technology Center		Pratt and Whitney Aircraft	
P.O. Box 226144		GPD, Mail Stop R-16	_
Attn: R. C. Van Siclen	1	Attn: Roy T. Debski	1
Dallas, TX 75266		West Palm Beach, FL 33410	

	Copies		Copies
Lockheed Missile & Space		University of Texas	
Company, Inc.		Professor Harris L. Marcus	
P.O. Box 504		Tay 167	
Dept. 62-60, Bldg. 104		Austin, TX 78712	1
Attn: Henry Cohan	1		
Sunnyvale, CA 94086		Gould, Inc.	
		Program Manager	
Fiber Materials, Inc West		40 Gould Center	
11222 La Genega Blvd.		Attn: Brian L. Burrows	1
Suite 320		Rolling Meadows, IL 60008	
Attn: John Cooney	1		
Inglewood, CA 90304		Office of Naval Research	
		536 S. Clark Street	
Ballistic Missile Defense		Attn: Dr. G. Sandoz	
Materials		Chicago, IL 60605	
Program Office			
Bldg. 131		Defense Documentation Center	
Army Materials and Mechanics		Cameron Station	
Research Center		Alexandria, VA 22314	12
Attn: Lewis R. Aronin	1		
Watertown, MA 02172		Office of Chief of Naval	
		Operations	
NAVPRO, Sunnyvale		Operation Evaluation Group	
SPL-3123		Washington, DC 20350	1
Lockheed Bldg. 181		•	
Attn: Philip R. Barlow	1	Defense Nuclear Agency	
Sunnyvale, CA 94086		Washington, DC 20301	2
•			
AFML/MB		Measurements Technology Inc.	
Attn: Davis R. Beeler	1	3029 Greer Road	
WPAFB, OH 45433		Attn: M. F. Duggan	1
		Palo Alto, CA 94303	
Charles Stark Draper Laboratory			
555 Technology Square		Naval Ocean Systems Center	
Attn: John Bimshas, MS #27	1	Attn: P. D. Burke, Code 932	1
Cambridge, MA 02139		San Diego, CA 92152	

DISTRIBUTION (Cont.)

	Copies		Copies
Applied Research Laboratory		US Army Electronics Command	
P.O. Box 30		Attn: D. Linden, Code DRSEL-	
Attn: H. M. Frost	1	TL-P	1
State College, PA 16801		Dr. S. Gilman	-
		Code DRSEL-TL-P	1
ARTECH Corporation		Fort Monmouth, NJ 07703	
2901 Telestar Ct.		Naval Weapons Center	
Attn: H. Hahn	1	Attn: Dr. Aaron Fletcher	1
Falls Curch, VA 22042		China Lake, CA 93555	1
		China bake, CA 93355	
Great Lakes Carbon Corporation		Defense Nuclear Agency	
299 Park Avenue		Attn: Library	1
Attn: W. R. Benn	1	Washington, DC 20301	•
New York, NY 10017			
		Headquarters, USAFSS	
U.S. Army Mobility Equipment		Air Force Special Communications	
Research and Development Command		Center	
Attn: G. D. Farmer Jr.,		Attn: Library	1
Code DRDNE EC	1	San Antonio, TX 78243	
Fort Belvoir, VA 22060	•		
TOTE BETVOIT, VA 22000		Harry Diamond Laboratory	
Army Foreign Science and	*	Chief Power Supply Branch	
Technology Center		Attn: A. A. Benderly	
220 7th Street		Code DRXDO-RDD	1
Attn: J. F. Crider, Code		2800 Powder Mill Road	
FSTC/DRXST-MTI	1	Adelphi, MD 20783	
Charlottesville, VA 22901			
		Naval Intelligence Support Center	
Headquarters, US Army Development	&	Attn: Dr. H. E. Ruskie	
Readiness Commind		Code 362	1
Attn: J. W. Crellin		4301 Suitland Road	
Code DRCDE-L	1	Washington, DC 20390	
5001 Eisenhower Avenue			

Alexandria, VA 22333

	Copies		Copies
Naval Material Command		NASA Goddard Space Flight Center	
Attn: I. Jaffe	•	Attn: G. Halpert	,
Code NAVMAT 0323	1	Code 771	1
R. H. Abrams		Greenbelt, MD 20771	
Code NAVMAT 03533	1		
Washington, DC 20360		Headquarters, Dept. of Transportati	on
Marcal Deliveration Contains Contain		Attn: R. Potter	,
Naval Underwater Systems Center		Code GEOE-3/61	1
Attn: T. Black	,	US Coast Guard, Ocean Engineering	
Code 3642	1	Division	
Newport, RI 02840		Washington DC 20590	
Naval Undersea Center		Edgewood Arsenal	
Attn: Library		Attn: Library	1
Code 6565	1	Aberdeen Proving Ground, MD 21010	
San Diego, CA 92132			
		Naval Electronics Systems Command	
Naval Weapons Support Center		Attn: A. H. Sobel, Code PME 124-31	. 1
Electrochemical Power Sources		Washington, DC 20360	
Division			
Attn: D. G. Miley		EPRI	
Code 305	1	Battery Technology	
Crane, IN 47522		Attn: D. L. Douglas	
		3412 Hillview Avenue	
Department of Energy		P. O. Box 10412	
Division of Electric Energy Systems		Palo Alto, CA 94303	
Attn: L. J. Rodgers			
Room 2101	1	J.P.L.	
Washington, DC 20545		California Institute of Technology	
		Attn: Dr. D. B. Edwards	1
Department of Energy		Mr. W. E. Rippel	1
Division of Applied Technology		4800 Oak Grove Drive	
Attn: Dr. A. Landrebe		Pasadena, CA 91103	
Code M/S E-463	1		
Washington, DC 20545			
Strategic Systems Project Office			
Engineering Development Project Off	ice		
Attn: K. N. Boyley			
Code NSP-2721	1		
Washington, DC 20360	•		
masning con, DC 20300			

TO AID IN UPDATING THE DISTRIBUTION LIST FOR NAVAL SURFACE WEAPONS CENTER, WHITE OAK LABORATORY TECHNICAL REPORTS PLEASE COMPLETE THE FORM BELOW:

TO ALL HOLDERS OF NSWC/TR 80-239

DO NOT RETURN THIS FORM IF ALL INFORMATION IS CURRENT

A. FACILITY NAME AND ADDRESS (OLD)	(Show Zip Code)	<u> </u>			
		· · · · ·		• •	
		,			
NEW ADDRESS (Show Zip Code)					
					•
					•
. ATTENTION LINE ADDRESSES:				-,	
c.					
REMOVE THIS FACILITY FROM THE	E DISTRIBUTION LIS	T FOR TECHNICA	L REPORTS O	N THIS SUBJECT	
, Namo C viva viva viva					
D.					

DEPARTMENT OF THE NAVY
NAVAL SURFACE WEAPONS CENTER
WHITE OAK, SILVER SPRING, MD. 20910

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

POSTAGE AND FEES PAID DEPARTMENT OF THE NAVY DOD 316



COMMANDER
NAVAL SURFACE WEAPONS CENTER
WHITE OAK, SILVER SPRING, MARYLAND 20910

ATTENTION: CODE R32

